

Eaton EPDU MI 2U In: 309 32A 1P - Out: C13x12:C19x4



DESCRIPTION

Button mounting on rear and sides, variable mounting bracket. 1U/2U form factor ePDUs can be mounted horizontally, vertically, or under a surface.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMIH06

Design :

Type : Single-phase

Caractéristiques :

Certification : CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011 Safety - Part 1: General Requirements, IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1 EN 55022:2010, EN 61000-6-2:2005 Part 6-2, EN 50581 : 2012, REACH, WEEE, PEP, ISO 9001:2008, ISO 14001:2004

AC input frequency : 50 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 16 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 482.6 mm

Dimensions (WxDxH) : 88.9 x 482.6 x 127 mm

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 127 mm

Input connection type : IEC-320-C20

Management protocols : SNMP, Telnet

Maximum current : 32 A

Maximum input current per phase : 32 A

Maximum power : 7400 W

Monitoring : Current

Mounting : Horizontal/Vertical

Nominal input voltage : 230 V

Nominal output voltage : 230 V

Operating temperature (T-T) : 0 - 60 °C

Output connections : 12 x C13 & 4 x C19

Package weight : 4.7 kg

PDU types : Metered

Power plug : IEC 60309

Product colour : Black

Rack capacity : 2U

Rack mount kit : Y

Rack mounting : Y

Supported network protocols : HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Sustainability certificates : RoHS

Width : 88.9 mm