

EPDU MI 0U (309 16A 3P)36XC13:6XC19



DESCRIPTION

New ePDU G3 Metered Input models feature best-in-class technologies, including $\pm 1\%$ billing grade accuracy, an advanced LCD pixel display, a hot-swap meter and the ability to daisy chain four ePDUs to share the same network connection and IP address.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMIB00

Design :

Type : Three-phase

AC input frequency : 50 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 42 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 1829 mm

Dimensions (WxDxH) : 52 x 1829 x 53 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 53 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 16 A

Maximum input current per phase : 16 A

Maximum power : 11000 W

Mounting : Vertical

Nominal input voltage : 400 V

Nominal output voltage : 230 V

Operating temperature (T-T) : 0 - 60 °C

Output connections : 36 x C13 & 6 x C19

Package weight : 5.72 kg

PDU types : Metered

Power plug : IEC 60309

Product colour : Black

Rack capacity : 0U

Rack mount kit : Y

Rack mounting : Y

Sustainability certificates : RoHS

Weight : 4.72 kg

Width : 52 mm