

BOSCH- Flexidome Panoramic 5100i 6 Mps NDS-5703-F360



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NDS-5703-F360LE

Représentation / réalisation :

Type : IP security camera

Alarm input/output : Yes

Audio system full duplex : Yes

Back Light Compensation (BLC) : Yes

Behavior analysis : Line crossing detection

Built-in microphone : Yes

Camera pan control : Yes

Camera shutter speed : 1/1.875 to 1/150000

Camera shutter type : Electronic

Compatible memory cards : SD, SDHC, SDXC

Connectivity technology : Wired

Country of origin : Thailand

Day/night mode : Yes

Detection distance : 20 m

Diameter : 14.8 cm

Ethernet interface type : Gigabit Ethernet

Ethernet LAN : Yes

Ethernet LAN (RJ-45) ports : 1

Focus : Motorized

Form factor : Bullet

Frame rate : 30 fps

HDMI ports quantity : 1

Height : 70 mm

IK code : IK10

Image quality adjustment : Brightness, Saturation, Sharpness
Infrared (IR) cut-off filter : Yes
International Protection (IP) code : IP66
Maximum resolution : 1920 x 1080 pixels
Mounting type : Ceiling
Networking standards : IEEE 802.3af
Night vision : Yes
Number of cameras : 12
Number of effective pixels (H x V) : 2.112 x 2.112 pixels
Number of lenses : 1
Number of Privacy masking areas : 8
Number of sensors : 1
Operating temperature (T-T) : -40 - 50 °C
Optical sensor size : 25.4 / 1.8 mm (1 / 1.8»)
Pan range : 0 - 355°
Pixel counter : Yes
Placement supported : Indoor & outdoor
Power consumption (Power over Ethernet (PoE)) : 6 W
Power source type : PoE
Product colour : White
Protection features : Impact resistant
Quality of Service (QoS) support : Yes
RAM capacity : 2.048 MB
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) (panoramic camera) : 50 dB
Storage relative humidity (H-H) : 0 - 98%
Storage temperature (T-T) : -40 - 70 °C
Supported network protocols : IPv4; IPv6; UDP; TCP; HTTP; HTTPS; RTP/RTCP; IGMP V2/V3; ICMP; ICMPv6; RTSP; FTP; ARP; DHCP; APIPA (Auto-IP, link local address); NTP (SNTP); SNMP (V1, MIBII); SNMP (V3, MIBII); 802.1x, EAP/ TLS; DNS; DNSv6; DDNS (DynDNS.org, selfHOST.de, noip.com); SMTP; iSCSI; UPnP (SSDP); DiffServ (QoS); LLDP; SOAP; CHAP; Digest authentication
Temperature sensor : Yes
Total megapixels : 6 MP
Video compression formats : H.264, M-JPEG, H.265, HEVC
Video recording : Yes
Voice codecs : AAC, G.711
Weight : 820 g
White balance : Auto, Manual