

Eaton 9PX 3000i RT2U Netpack Li-Ion



DESCRIPTION

Reliable. Versatile. Powerful. Efficient. With double-conversion topology for constant power conditioning and up to 93 percent efficiency, the Eaton 9PX 700-3000 VA models support your overall goal of business continuity. Its built for scalable deployment, features a graphical LCD for local status updates and integrates with virtualized environments.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 9PX3000IRTN-L

Design :

Certification : IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2, FCC Class B, CISPR22 Class B, CE /CB report (TUV) / cULus / EAC /RCM / KC / Energy Star

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 10 AC outlet(s)

Automatic battery test : Y

Battery technology : Lithium-Ion (Li-Ion)

Depth : 605 mm

Display type : LCD

Efficiency : 94%

Form factor : Rackmount/Tower

Harmonized System (HS) code : 85078000

Height : 86.5 mm

Hot-swap battery : Y

Input frequency : 40/70 Hz

Input operation voltage (max) : 276 V

Input operation voltage (min) : 176 V

Input power factor : 0.99

LED indicators : Y

Noise level : 40 dB

Number of input phases : 1

Number of output phases : 1

Operating altitude : 0 - 3000 m

Operating relative humidity (H-H) : 0 - 96%

Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 2400 W
Output power capacity : 3 kVA
Output power factor : 1
Power plug : C20 coupler
Power protection features : Battery discharge
Product colour : Black, Silver
Rack capacity : 2U
Rack mount kit : Y
RS-232 ports : 1
Safety : IEC/EN 62040-1, UL 1778, CSA 22.2
Serial interface : Y
Serial interface type : RS-232
Sustainability certificates : CE, ENERGY STAR
Typical backup time at full load : 10 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
USB port type : USB Type-B
Waveform : Sine
Weight : 22.9 kg
Width : 440 mm