

Eaton 5P 1550I



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 5P1550I
Design :
Certification : IEC/EN 62040-1, UL 1778, IEC/EN 62040 -2 , IEC/EN 62040-3 (Performance), CE, CB report (TUV)
AC outlet types : C13 coupler
AC outlets quantity : 8 AC outlet(s)
Automatic battery test : Y
Battery technology : Sealed Lead Acid (VRLA)
Bundled software : Intelligent Power Software suite
Depth : 445 mm
Display type : LCD
ECO mode : N
Efficiency : 98%
Form factor : Tower
Harmonized System (HS) code : 85078000
Height : 230 mm
Hot-swap battery : Y
Input connection type : IEC C14
Input frequency : 40/70 Hz
Input operation voltage (max) : 294 V
Input operation voltage (min) : 150 V
Mac compatibility : N
Management card included : N
Noise level : 40 dB
Nominal input voltage : 230 V
Nominal output voltage : 230 V
Number of input phases : 1

Number of output phases : 1
Operating temperature (T-T) : 0 - 35 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 1100 W
Output power capacity : 1.55 kVA
Power plug : C14 coupler
Product colour : Black
RS-232 ports : 1
Safety : EN 62040-1, UL 1778
Typical backup time at half load : 13 min
UPS topology : Line-Interactive
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 15.6 kg
Width : 150 mm