



DESCRIPTION

21.5 IPS technology panel with height adjustable stand and 100Hz refresh rate

Stylish edge-to-edge design makes the ProLite XUB2292HSU perfect for multi-monitor set-ups. The IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. The 100Hz refresh rate together with FreeSync function provides an instant, tangible improvement in image smoothness. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, USB 3.2 hub, headphone socket, HDMI and DisplayPort connections, a blue light reducer function to reduce eye fatigue and an ergonomic 150mm height adjustable stand for optimal user comfort, make this monitor a great choice for both multi-monitor configuration and office applications.

TECHNICAL CHARACTERISTICS

Brand : IIYAMA

Part number : XUB2292HSU-W6

Représentation / réalisation :

AMD FreeSync : Yes

Connectivité :

HDMI : Yes

HDCP : Yes

Ergonomie :

Pivot : Yes

AC input frequency : 50/60 Hz

AC input voltage : 100 - 240 V

AMD FreeSync type : FreeSync

Built-in camera : No

Built-in speaker(s) : Yes

Built-in USB hub : Yes

Cable lock slot : Yes

Cable lock slot type : Kensington

Cable management : Yes

Cables included : AC, HDMI, USB

Contrast ratio (dynamic) : 80000000:1

Contrast ratio (typical) : 1000:1

Depth (with stand) : 109.5 mm
Depth (without stand) : 109.5 mm
Display brightness (typical) : 250 cd/m ²
Display diagonal : 54.6 cm (21.5»)
Display diagonal (metric) : 56.7 cm
Display number of colours : 16.7 million colours
Display resolution : 1920 x 1080 pixels
Display surface : Matt
Display technology : LED
DisplayPorts quantity : 1
Energy consumption (SDR) per 1000 hours : 14 kWh
Energy efficiency class (HDR) : Not available
Energy efficiency class (SDR) : E
Energy efficiency scale : A to G
Flicker-free technology : Yes
HD type : Full HD
HDMI ports quantity : 1
Headphone out : Yes
Height (with stand) : 486.5 mm
Height (without stand) : 336.5 mm
Height adjustment : 15 cm
Horizontal scan range : 30 - 115 kHz
Low Blue Light technology : Yes
Market positioning : Business
Maximum refresh rate : 100 Hz
Native aspect ratio : 16:9
NTSC coverage (typical) : 72%
Number of speakers : 4
On Screen Display (OSD) : Yes
Package depth : 159 mm
Package height : 380 mm
Package type : Box
Package weight : 5.9 kg
Package width : 560 mm
Panel mounting interface : 100 x 100 mm
Panel type : IPS
Pivot angle : 90 - 90°
Pixel pitch : 0.248 x 0.248 mm
Power consumption (off) : 0.3 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 14 W
Power supply type : Internal
Product colour : White
Quick start guide : Yes
Response time : 0.4 ms
Screen shape : Flat
SRGB coverage (typical) : 99%
Swivel angle range : 45 - 90°
Swivelling : Yes
Tilt adjustment : Yes
Tilt angle range : 22 - 5°
Touchscreen : No
USB hub version : 3.2 Gen 1 (3.1 Gen 1)

VESA mounting : Yes
Viewable size, horizontal : 47.6 cm
Viewable size, vertical : 26.8 cm
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Wall mountable : Yes
Weight (with stand) : 4.5 kg
Width (with stand) : 489.5 mm
Width (without stand) : 489.5 mm