



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : HP

Part number : 89B68AA

### Réseau :

Bluetooth : No

Auto diagnostic : Yes

Syslog : Yes

Adaptive jitter buffers : Yes

Backlight display : Yes

Cables included : LAN (RJ-45)

Call forwarding : Yes

Call hold : Yes

Call pick up : Yes

Call transfer : Yes

Call waiting : Yes

Comfort noise generation (CNG) : Yes

Conference call : Yes

Depth : 62 mm

DHCP client : Yes

Display : LCD

Display diagonal : 8.89 cm (3.5»)

Display resolution : 320 x 240 pixels

Distinctive ring : Yes

Do not disturb function : Yes

Dual-Tone Multi-Frequency (DTMF) modes : In-band

Ethernet LAN : Yes

Ethernet LAN (RJ-45) ports : 2

Ethernet LAN data rates : 10,100,1000 Mbit/s

Ethernet LAN interface type : Gigabit Ethernet
Event logging : Yes
Frequency range : 150 - 7000 Hz
Front camera : No
Handset : ITU-T P.370, TIA 504A
Handset type : Wired handset
Harmonized System (HS) code : 85171800
Headset connectivity : RJ-9
Height : 262 mm
Integrated voicemail : Yes
Keypad number of keys : 12
Lines quantity : 6 lines
Management platform : HTML5, CSS, SSL
Number of handles included : 1 pc(s)
On-hook dialling : Yes
Operating relative humidity (H-H) : 5 - 95%
Operating temperature (T-T) : 0 - 40 °C
Power over Ethernet (PoE) : Yes
Product colour : Black
Product type : IP Phone
Quality of Service (QoS) support : Yes
Quick start guide : Yes
Redialing : Yes
RJ-9 ports quantity : 1
Safety : UL 60950-1 , CE Mark , CAN/CSA C22.2 No 60950-1 , EN 60950-1 , IEC 60950-1 , AS/NZS 60950-1
SIP registrar server : Yes
Speakerphone : Yes
Speed dialling : Yes
Storage relative humidity (H-H) : -40 - 70%
Touchscreen : No
Unicode UTF-8 character support : Yes
USB 2:0 ports quantity : 1
Voice activity detection : Yes
Voice codecs : G.711, G.722, G.722.1, G.729A, G.729B, OPUS, iLBC
Volume control : Digital
WAN connection type : RJ-45
Weight : 1.04 kg
Width : 233 mm
Wi-Fi : No