

ALLIED TELESIS AT-X230-10GT-50



DESCRIPTION

The Allied Telesis x230-10GT features 8 x 10/100/1000T ports with 2 SFP Gigabit uplink ports. The compact design provides flexible deployment options, and a full feature-set and compact design makes it ideal for applications at the network edge, supporting Gigabit to the desktop for maximum network performance.

TECHNICAL CHARACTERISTICS

Brand : ALLIED TELESIS	
Part number : AT-X230-10GT-50	
Main features :	
Network standard :	Gigabit
ODI Model Layer :	Layer 3
Management :	WEB+SNMP+RMON+CLI
Operating environment :	Professional
Industrial :	No
Rackmount :	Yes
PoE function :	No
Power supply :	Embedded power supply
Outband console port :	Yes
Temperature supported in operation :	0 to 50°C
Mounting system :	Optional kit
Connectors :	
Total number of ports :	12
Number of RJ-45 ports :	9
Number of fiber ports :	2
Number of BNC Ethernet ports :	0
RJ-45 patch cords :	
Number of 10/100 ports :	0
Number of 10G ports :	0
Number of ports Multi-Gigabit 10/100/1G/2.5G/5G :	0
Number of Gigabit ports :	8
Fiber optics :	

Number of 100FX ports : 0
Number of SFP Gigabit ports : 0
Number of SFP+ ports : 0
Number of ports QSFP 40G : 0
Number of SFP 1G/100 ports : 2
Number of SFP 100FX ports : 0
PoE data :
PoE standard : -
PoE budget (Watts) : 0
Number of 15-Watt PoE ports : 0
Number of 30-Watt PoE+ ports : 0
Number of 60-W PoE++ ports : 0
Dimensions :
Length (mm) : 275
Width (mm) : 210
Height (mm) : 42.5