

Mini Media Converter 10/100T to 100BASE-FX MM, LC connector



DESCRIPTION

The Allied Telesis MMC200 Series of Fast Ethernet mini media converters leverages its smaller size to not only help the environment with a small carbon footprint, but also to save space in its working environment. Despite its compact size, the MMC200 Series delivers all the power and functionality of standard size media converters.

TECHNICAL CHARACTERISTICS

Brand : ALLIED TELESIS

Part number : AT-MMC200/LC-60

Réseau :

Auto MDI/MDI-X : Y

Design :

Certification : EN55024, EN61000-3-2, EN61000-3-3

Connectivity technology : Wired

Converter input interface : 100Base-TX

Converter output interface : 100Base-FX

Depth : 101.6 mm

Ethernet interface type : Fast Ethernet

Ethernet LAN data rates : 10,100 Mbit/s

Fiber optic connector : LC

Height : 21.8 mm

Internal : N

Jumbo frames support : Y

LED indicators : Activity, Link

Maximum transfer distance : 2000 m

Networking standards : IEEE 802.1Q

Operating altitude : 0 - 3000 m

Operating relative humidity (H-H) : 5 - 95%

Operating temperature (T-T) : 0 - 50 °C

Power consumption (typical) : 1.7 W

Power over Ethernet (PoE) : Y

Product colour : Grey

Rx power (min) : -32 dBmW

Safety : FCC Class A, EN55022 Class A, CISPR 22 Class A, C-TICK, VCCI

Storage relative humidity (H-H) : 5 - 95%

Storage temperature (T-T) : -15 - 65 °C

Store-and-forward : Y

Tx power (max) : -14 dBmW

Tx power (min) : -20 dBmW

Wavelength : 1310 nm

Weight : 170 g

Width : 56 mm