

ATEN Control System VK1100A - Compact Control Box Gen2



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN
Part number : VK1100A-AT-G
AC input frequency : 50/60 Hz
AC input voltage : 100 - 240 V
Built-in display : N
Cabling technology : 10/100/1000Base-T(X)
Country of origin : Taiwan
DC-in jack : Y
Depth : 200 mm
Ethernet interface type : Gigabit Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Ethernet LAN data rates : 10,100,1000 Mbit/s
Heat dissipation : 83 BTU/h
Height : 44 mm
Housing material : Metal
Internal memory : 0.512 GB
Internal memory type : SDRAM
Internal storage capacity : 8 GB
IR connectivity : Y
LED indicators : Y
License quantity : 2 license(s)
Manual : Y
Master (outer) case volume : 36528.73 cm³
Number of analog I/O pins : 3
Number of relay pins : 8
On/off switch : Y

Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 50 °C
Package depth : 414 mm
Package height : 117 mm
Package type : Box
Package volume : 16423.77 cm ³
Package weight : 1.8 kg
Package width : 207 mm
Power consumption (max) : 4.5 W
Power consumption (typical) : 4.3 W
Power cord included : Y
Power supply location : Internal
Processor cores : 4
Product colour : Black
Reset button : Y
RS-232 ports : 2
RS-422 ports : 1
RS-485 ports : 1
Serial interface type : RS-232, RS-232/422/485
Storage media type : Flash
Storage temperature (T-T) : -20 - 60 °C
Supported network protocols : ARP, ICMP, TCP/IP, DHCP, HTTPS, SSH
Terminal block included : Y
USB port : Y
USB port type : USB Type-A
USB ports quantity : 1
Weight : 1.19 kg
Width : 164.1 mm