

INFOSEC UPS E4 LCD Pro 15 KVA Tri-Mono



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : INFOSEC

Part number : 67509

Design :

Certification : CE

AC outlet types : Terminal

Audible alarm modes : Alarm when on battery, Fault, Low battery alarm, Overload alarm

Audible alarm(s) : Y

Battery capacity : 9 Ah

Battery recharge time : 9 h

Battery technology : Sealed Lead Acid (VRLA)

Battery voltage : 12 V

Cables included : RS-232, USB cable

Charging current : 4 A

Cold start : Y

Crest factor : 3:1

Depth : 442 mm

Display type : LCD

Efficiency : 91%

Emergency Power Off (EPO) : Y

Emergency Power Off (EPO) connector : Y

Form factor : Tower

Height : 668 mm

Input frequency : 46/64 Hz

Input operation voltage (max) : 520 V

Input operation voltage (min) : 190 V

Input power factor : 0.8

Manual : Y

Noise level : 60 dB
Number of input phases : 3
Number of output phases : 1
Operating altitude : 0 - 1000 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 46/64 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 208 V
Output power : 12000 W
Output power capacity : 15 kVA
Output voltage regulation : -1 - 1%
Output voltage Total Harmonic Distortion (THD) : 6%
Package weight : 82.4 kg
Power factor : 0.8
Product colour : Black
Serial interface : Y
Serial interface type : RS-232
Sustainability certificates : RoHS
Typical backup time at half load : 12 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
USB port type : USB Type-B
Waveform : Pure sine
Weight : 78 kg
Width : 190 mm