

HANWHA- Indoor Camera XND-8081REV



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XND-8081REV

Représentation / réalisation :

Type : IP security camera

Active tampering alarm : Y

Alarm input/output : Y

Alert notification type : E-mail

Angle of rotation : 355°

Anti-flicker : Y

Auto-tracking : Y

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)

Camera pan control : Y

Camera shutter speed : 2 - 1/12000 s

Camera shutter type : Electronic

Camera tilt control : Y

Card reader integrated : Y

Closest focusing distance : 0.5 m

Compatible memory cards : MicroSD (TransFlash), SDHC, SDXC

Composite video out : 1

Connectivity technology : Wired

Day/night mode : Y

Detect distance (tele) : 146 m

Detect distance (wide) : 49.4 m

Diameter : 16 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Flip & mirror : Y
Focal length range : 3.9 - 9.4 mm
Focus : Motorized
Fog proof : Y
Form factor : Dome
Frame rate : 60 fps
Height : 125 mm
Highlight Compensation (HLC) : Y
Housing material : Aluminium
HTTPS encryption : Y
Identify distance (tele) : 15 m
Identify distance (wide) : 4.9 m
IK code : IK10
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP56
IP address filtering : Y
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
LED type : IR
Lens viewing angle, diagonal : 119.9°
Lens viewing angle, horizontal : 92.1°
Lens viewing angle, vertical : 67.2°
Maximum aperture number : 1.3
Maximum memory card size : 512 GB
Maximum resolution : 2560 x 1920 pixels
Minimum illumination : 0.07 lx
Mirror : Y
Motion sensor : Y
Mounting type : Ceiling
Networking standards : IEEE 802.3at
Night vision : Y
Night vision distance : 50 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 2560 x 1920 pixels
Number of languages : 17
Number of lenses : 1
Number of sensors : 1
Number of users : 20 user(s)
Observe distance (tele) : 58 m
Observe distance (wide) : 19.7 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -25 - 60 °C
Optical sensor size : 25.4 / 1.8 mm (1 / 1.8»)
Optical zoom : 2.4x
Pan range : 0 - 360°
Password protection : Y
Placement supported : Indoor & outdoor
Power consumption (max) : 25.5 W
Power consumption (Power over Ethernet (PoE)) : 12.95 W

Power consumption (typical) : 10.2 W
Power source type : PoE
Privacy masking : Y
Privacy protection : Y
Product colour : White
Progressive scan : Y
Quality of Service (QoS) support : Y
Recognize distance (tele) : 29 m
Recognize distance (wide) : 9.9 m
Sample rate : 16 kHz
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2560 x 1440, 2560 x 1920
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTP
Tilt angle range : -45 - 85°
Total megapixels : 6 MP
USB port : Y
Video compression formats : H.264, H.265, M-JPEG
Video formats support