

HANWHA- IR IP camera bullet 4 Mps QNO-7032R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QNO-7032R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Alarm output channels : 1
Audio input channels : 1
Camera shutter speed : 1/5~1/12,000 s
Camera shutter type : Electronic
Connectivity technology : Wired
Day/night mode : Y
Detect distance (wide) (panoramic camera) : 112.3 m
Diameter : 7 cm
Dynamic range : 120 dB
Ethernet LAN : Y
Fixed focus : Y
Focal length range (panoramic camera) : 6 mm
Form factor : Bullet
Gain control type : Auto/Manual
Height : 246 mm
Housing material : Aluminium
Identify distance (wide) (panoramic camera) : 11.2 m
IK code : IK10
International Protection (IP) code : IP66
Maximum aperture number (panoramic camera) : 2
Maximum resolution : 2560 x 1440 pixels

Minimum illumination : 0.15 lx
Mounting type : Ceiling/Wall/Pole
Night vision : Y
Number of cameras : 1
Number of lenses : 1
Observe distance (wide) (panoramic camera) : 44.9 m
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Placement supported : Outdoor
Power consumption (max) : 10.7 W
Power consumption (typical) : 8 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Grey
Recognize distance (wide) (panoramic camera) : 22.5 m
Sensor type : CMOS
Storage temperature (T-T) : -40 - 60 °C
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP
Total megapixels : 4 MP
Video compression formats : H.264, H.265, M-JPEG
Video formats supported : H.264, H.265, M-JPEG
Video motion detection : Y
Weight : 700 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wi-Fi : N