

PHILIPS- Signage screen 65" 65BDL3650QE/00



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : PHILIPS	
Part number : 65BDL3650QE/00	
Connectivité :	
RS-232C :	Yes
AC input frequency :	50-60 Hz
AC input voltage :	100-240 V
Audio input :	1
Audio output :	1
Batteries included :	Yes
Bezel width (bottom) :	1.49 cm
Bezel width (side) :	1.49 cm
Bezel width (top) :	1.49 cm
Built-in processor :	Yes
Built-in speaker(s) :	Yes
Cables included :	AC, IR sensor, RS-232
Card reader integrated :	Yes
Compatible memory cards :	MicroSD (TransFlash)
Computer system :	Yes
Computer system type :	System on Chip (SoC)
Contrast ratio (dynamic) :	500000:1
Contrast ratio (typical) :	1200:1
Display brightness :	300 cd/m²
Display depth :	68.9 mm
Display diagonal :	165.1 cm (65»)
Display diagonal (metric) :	163.9 cm
Display height :	837.3 mm
Display number of colours :	1.07 billion colours

Display resolution : 3840 x 2160 pixels
Display technology : LCD
Display weight : 28.5 kg
Display width : 1462.3 mm
DVI port : Yes
DVI-I ports quantity : 1
Energy efficiency class (SDR) : G
Energy efficiency scale : A to G
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Haze rate : 2%
HD type : 4K Ultra HD
HDMI ports quantity : 2
HDMI version : 2.0
Infrared data port : Yes
Internal memory : 3 GB
Internal storage capacity : 16 GB
LED backlight : Yes
LED backlighting type : Direct-LED
Mean time between failures (MTBF) : 50000 h
Native aspect ratio : 16:9
Native refresh rate : 60 Hz
Number of built-in speakers : 2
On Screen Display (OSD) : Yes
Operating hours (hours/days) : 18/7
Operating relative humidity (H-H) : 20 - 80%
Operating system installed : Android 10
Operating temperature (T-T) : 0 - 40 °C
OPS module slot : Yes
Orientation : Horizontal/Vertical
Panel mounting interface : 400 x 400 mm
Panel type : ADS
Pixel pitch : 0.372 x 0.372 mm
Placement supported : Indoor
Power consumption (max) : 310 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 153 W
Processor architecture : ARM Cortex-A55
Processor cores : 4
Processor family : ARM Cortex
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal
Quick start guide : Yes
Remote control included : Yes
Response time : 8 ms
RMS rated power : 20 W
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -20 - 60 °C
Touchscreen : No
USB port : Yes
USB ports quantity : 3
USB version : 2.0/3.2 Gen 1 (3.1 Gen 1)

VESA mounting : Yes
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Wi-Fi : Yes