

# BOSCH NIN-73023-A10A



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NIN-73023-A10A

### Représentation / réalisation :

Type : IP security camera

### Système d'objectif :

Auto focus : Y

Alarm input/output : Y

Analog signal format system : NTSC, PAL

Angle of rotation : 270°

Audio formats supported : G.711, AAC-LC

Audio system full duplex : Y

Auto-tracking : Y

BNC output ports : 1

Camera pan control : Y

Camera shutter speed : 1/25 - 1/15000 s

Camera shutter type : Electronic

Camera tilt control : Y

Card reader integrated : Y

Compatible memory cards : MicroSDHC, MicroSDXC

Composite video out : 1

Connectivity technology : Wired

Day/night mode : Y

Diameter : 15.8 cm

Digital watermark : Y

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

|   |
|---|
| Flip & mirror : Y   |
| Focal length range : 10 - 23 mm   |
| Focus : Motorized   |
| Focus adjustment : 1.6  |
| Form factor : Dome  |
| Frame rate : 60 fps   |
| Height : 124 mm   |
| Housing material : Aluminium, Polycarbonate (PC)  |
| IK code : IK10  |
| Image quality adjustment : Brightness, Contrast, Sharpness, Saturation  |
| International Protection (IP) code : IP66   |
| Lens viewing angle, horizontal : 32°  |
| Lens viewing angle, vertical : 18°  |
| Maximum memory card size : 2000 GB  |
| Maximum resolution : 1920 x 1080 pixels   |
| Mounting type : Ceiling   |
| Networking standards : IEEE 802.3af   |
| Noise reduction : Y   |
| Number of cameras : 1   |
| Number of effective pixels (H x V) : 1920 x 1080 pixels   |
| Operating relative humidity (H-H) : 5 - 93%   |
| Operating temperature (T-T) : -30 - 50 °C   |
| Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)  |
| Pixel counter : Y   |
| Placement supported : Indoor & outdoor  |
| Power consumption : 600 mA  |
| Power consumption (max) : 7.2 W   |
| Power source type : DC, PoE   |
| Privacy masking : Y   |
| Product colour : Black, White   |
| Protection features : Scratch resistant   |
| Region of Interest (ROI) encoding : Y   |
| Sample rates : 8 - 16 kHz   |
| Security algorithms : 3DES, MD5, SSL/TLS, DES, SHA-1, SHA-256   |
| Sensor type : CMOS  |
| Signal-to-Noise Ratio (SNR) : 50 dB   |
| Storage temperature (T-T) : -50 - 70 °C   |
| Supported graphics resolutions : 512 x 288, 704 x 480, 768 x 432, 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)  |
| Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, noip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, digest authentication |
| Supported video modes : 720p, 1080p   |
| Time stamp overlay : Y  |
| Total megapixels : 2 MP   |
| Video formats supported : H.264, M-JPEG   |
| Video recording : Y   |
| Video streaming : Y   |
| Web browser : Y   |
| Weight : 850 g  |
| White balance : Sodium lamp, Auto, Manual   |
| Wide Dynamic Range (WDR) : Y  |
| Zoom capability : Y   |