

HANWHA- IP Camera QNV-6032R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : QNV-6032R

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Alarm input/output : Y

Alert notification type : E-mail

Angle of rotation : 355°

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)

Built-in HDD : N

Camera pan control : Y

Camera shutter speed : 1/5 - 1/12000 s

Camera shutter type : Electronic

Camera tilt control : Y

Card reader integrated : Y

Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC

Composite video out : 1

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12

DC-in jack : Y

Diameter : 12 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

| |
|--|
| Fixed focal length : 6 mm |
| Fixed focus : Y |
| Flash memory : 512 MB |
| Flip & mirror : Y |
| Form factor : Dome |
| Frame rate : 30 fps |
| Housing material : Aluminium |
| IK code : IK10 |
| Infrared (IR) cut-off filter : Y |
| Intelligent Video Surveillance (IVS) system features : Defocus |
| Internal memory : 256 MB |
| International Protection (IP) code : IP66 |
| IP address filtering : Y |
| Languages support : Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Swedish, Turkish |
| LED type : IR |
| Length : 91.7 mm |
| Lens viewing angle, diagonal : 60.4° |
| Lens viewing angle, horizontal : 52.8° |
| Lens viewing angle, vertical : 30.3° |
| Mac operating systems supported : Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave |
| Maximum aperture number : 2 |
| Maximum memory card size : 128 GB |
| Maximum resolution : 1920 x 1080 pixels |
| Microphone in : Y |
| Mounting type : Ceiling/wall |
| Networking standards : IEEE 802.11ax, IEEE 802.1af |
| Night vision : Y |
| Night vision distance : 30 m |
| Noise reduction : Y |
| Number of cameras : 1 |
| Number of languages : 17 |
| Number of lenses : 1 |
| Number of sensors : 1 |
| Number of users : 6 user(s) |
| Operating relative humidity (H-H) : 0 - 90% |
| Operating temperature (T-T) : -30 - 55 °C |
| Optical sensor size : 50.8 / 28 mm (2 / 28») |
| Pan range : 0 - 350° |
| Password protection : Y |
| Password protection type : User |
| Placement supported : Outdoor |
| Power consumption (max) : 6.4 W |
| Power consumption (Power over Ethernet (PoE)) : 7.4 W |
| Power consumption (typical) : 5.1 W |
| Power source type : DC, PoE |
| Privacy masking : Y |
| Product colour : White |
| Quality of Service (QoS) support : Y |
| Security algorithms : EAP-TLS, HTTPS, LEAP |
| Sensor type : CMOS |
| Streaming method : Multicast, Unicast |
| Supported graphics resolutions : 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080) |

| |
|--|
| Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP |
| Tilt angle range : 0 - 67° |
| Total megapixels : 2 MP |
| Video compression formats : H.264, H.265, M-JPEG |
| Video streaming : Y |
| Voice codecs : G.711ulaw, G.726 |
| Weight : 510 g |
| White balance : ATW, AWC, Indoor, Manual, Outdoor |
| Wide Dynamic Range (WDR) : Y |
| Wi-Fi : N |
| Windows operating systems supported : Windows 10, Windows 7 |