



DESCRIPTION

The TL-SM5110-SR is designed to extend transfer distances based on 10Gbps Ethernet connectivity. It is a 10GBASE-SR high performance 850nm multi-mode SFP+ transceiver. It supports full duplex, 10G Ethernet connections up to 300m or 33m with 50/125µm or 62.5/125µm fiber cables respectively.

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : SM5110-SR
Caractéristiques :
Certification : FCC, CE
Digital Diagnostics Monitoring (DDM) : Yes
Fiber cable diameters supported (core/cladding) : 50/125,62.5/125 µm
Fiber optic connector : LC (UPC)
Harmonized System (HS) code : 85369010
Hot-swap : Yes
Input voltage : 3.3 V
Interface type : SFP+
Maximum data transfer rate : 10000 Mbit/s
Maximum transfer distance : 300 m
Multi-mode fiber (MMF) supported : Yes
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 70 °C
Product colour : Silver
SFP transceiver type : Fiber optic
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 80 °C
Wavelength : 850 nm