

Eaton 3S 550 FR



DESCRIPTION

Eaton 3S provides power and surge protection for desktop computers, wireless networks, gaming consoles, and other critical equipment in your home or business.

TECHNICAL CHARACTERISTICS

Brand : EATON	
Part number : 3S550F	
Design :	
Certification :	CE/EAC/Ukr/Cm/CB report
AC outlets quantity :	6 AC outlet(s)
Automatic battery test :	Y
Battery technology :	Sealed Lead Acid (VRLA)
Cable length :	1.5 m
Cold start :	Y
Depth :	140 mm
Harmonized System (HS) code :	85078000
Height :	86 mm
Hot-swap battery :	N
Input frequency :	50/60 Hz
Input operation voltage (max) :	284 V
Input operation voltage (min) :	161 V
LED indicators :	Y
Maximum current :	10 A
Nominal input voltage :	230 V
Operating altitude :	0 - 3000 m
Operating temperature (T-T) :	0 - 40 °C
Output frequency :	50 Hz
Output operation voltage (max) :	240 V
Output operation voltage (min) :	220 V
Output power :	330 W
Output power capacity :	0.55 kVA

Power protection features : Overdischarge
Product colour : Black, White
Safety : IEC 62040-1; IEC 62040-2 C2; IEC 62040-3; IEC 62040-4; IEC 61643-11
Surge protection : Y
UPS topology : Standby (Offline)
USB 2:0 ports quantity : 1
USB port : N
Weight : 3.2 kg
Width : 325 mm