

# LEGRAND UPS Keor SP 1000 VA, IEC and CE 7/5 sockets



## DESCRIPTION

The Keor SP is a single phase uninterruptible power supply with line interactive technology. It delivers a rated power of 600-800-1000-1500-2000VA, it is CPU-controlled and is equipped, internally, with valve-regulated, hermetically sealed lead accumulator batteries.

The presence of an electronic stabilizer (AVR) inside the UPS provides the connected loads with effective protection against any interference in the electrical mains.

## TECHNICAL CHARACTERISTICS

Brand : LEGRAND

Part number : 310191

### Design :

Certification : EN 62040-1, EN 62040-2

AC outlet types : C13 coupler, Type E

AC outlets quantity : 4 AC outlet(s)

Audible alarm(s) : Y

Auto shut-off : N

Automatic Voltage Regulation (AVR) : Y

Battery capacity : 9 Ah

Battery technology : Sealed Lead Acid (VRLA)

Depth : 380 mm

Efficiency : 97%

Form factor : Mini Tower

Height : 173 mm

Input frequency : 45/65 Hz

Input operation voltage (max) : 280 V

Input operation voltage (min) : 170 V

LED indicators : Y

Manual : Y

Master (outer) case gross weight : 11.8 kg

Master (outer) case height : 265 mm

Master (outer) case length : 465 mm
Master (outer) case width : 243 mm
Noise level : 40 dB
Number of batteries supported : 2
Number of input phases : 1
Number of output phases : 1
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output frequency regulation : 1 Hz
Output operation voltage (max) : 253 V
Output operation voltage (min) : 207 V
Output power : 900 W
Output power capacity : 1.5 kVA
Output power factor : 0.6
Output voltage regulation : 10%
Package depth : 9.73 mm
Package height : 173 mm
Package weight : 11.2 kg
Package width : 148 mm
Pallet net height : 125 cm
Pallet net length : 100 cm
Pallet net weight : 473 kg
Pallet net width : 120 cm
Potential-free output : N
Power plug : C14 coupler
Power protection features : Overcharge, Overdischarge, Overload, Short circuit
Power source type : AC
Product colour : Black, White
Products per master (outer) case : 1 pc(s)
Products per pallet : 40 pc(s)
Serial interface : Y
Surge protection : Y
Sustainability certificates : CE
Sustainability compliance : Y
UPS topology : Line-Interactive
USB 2:0 ports quantity : 2
USB port : Y
USB port type : USB Type-A/USB Type-B
Waveform : Sine
Weight : 10.5 kg
Width : 148 mm