



DESCRIPTION

The Eaton 9E UPS constantly monitors power conditions and regulates voltage and frequency thanks to the double conversion topology. Eaton 9E UPS can power more servers than most similar UPS because of a 0.8 power factor.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 9E1000I

Design :

Certification : IEC/EN 62040 -2, CE, CB report (TUV)

AC outlet types : IEC 320

AC outlets quantity : 4 AC outlet(s)

Depth : 144 mm

Efficiency : 91%

Height : 356 mm

Input frequency : 50/60 Hz

Input operation voltage (max) : 300 V

Input operation voltage (min) : 100 V

Noise level : 37 dB

Operating temperature (T-T) : 0 - 40 °C

Output frequency : 50/60 Hz

Output operation voltage (max) : 240 V

Output operation voltage (min) : 208 V

Output power : 800 W

Output power capacity : 1 kVA

Overload capacity (1 minute) : 130%

Overload capacity (10 seconds) : 150%

Overload capacity (5 minute) : 150%

Power plug : C13 coupler

RS-232 ports : 1

Safety : IEC/EN 62040-1

Serial interface : Y

Serial interface type : RS-232

Serial ports quantity : 1

Typical backup time at full load : 4 min

Typical backup time at half load : 12 min

UPS topology : Double-conversion (Online)

USB port : Y

Weight : 9.5 kg

Width : 228 mm