



DESCRIPTION

The AMS115 compact subwoofer features a 15-inch neodymium transducer and offers low frequency down to 35 Hz. With a lightweight enclosure, ergonomic handles, M20 threaded pole mount, and 12 M10 suspension points, this passive subwoofer is ideal for a variety of applications in portable setups or permanent installations especially when paired with Bose AMM multipurpose loudspeakers. For example, combine an AMM112 with the AMS115 subwoofer for fill applications. Or, for front-of-house applications, combine an AMM108 and AMS115 sub to give audiences an impactful, full-spectrum audio experience.

Compact high-output design with a lightweight, 15-inch neodymium transducer, low frequency down to 35 Hz, and 130 dB peak output

Direct-radiating bass reflex-tuned enclosure with large, ergonomic handles and caster mounting points

Pair with Bose PowerMatch amps and ControlSpace DSP for best performance and loudspeaker protection

Deploy easily in permanent or portable applications with 28 kg (63 lb) design featuring 12 M10 threaded inserts for suspension in permanent installations and integrated M20 threaded pole mount for use in temporary applications

TECHNICAL CHARACTERISTICS

Brand : BOSE
Part number : 843163-0110
Impedance : 8
Material : Plywood
Package weight : 33.3 kg
Product colour : Black
Subwoofer crossover frequencies : 40 - 100 Hz
Subwoofer depth : 50.8 cm
Subwoofer driver diameter : 38.1 cm
Subwoofer driver diameter (imperial) : 38.1 cm (15»)
Subwoofer frequency range : 35 - 130 Hz
Subwoofer height : 47 cm
Subwoofer peak power : 2800 W
Subwoofer RMS power : 500 W
Subwoofer sensitivity : 96 dB
Subwoofer type : Active subwoofer

Subwoofer weight : 28.4 kg

Subwoofer width : 47 cm