

HANWHA IP camera XND-6020R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XND-6020R
Représentation / réalisation :
Type : IP security camera
Active tampering alarm : Y
Alarm input/output : Y
Alert notification type : E-mail
Angle of rotation : 355°
Audio detection : Y
Audio formats supported : AAC-LC, ADPCM, G.711
Auto-tracking : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Camera pan control : Y
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Camera tilt control : Y
Card reader integrated : Y
Closest focusing distance : 0.4 m
Compatible memory cards : SD, SDHC, SDXC
Composite video out : 1
Connectivity technology : Wired
Depth : 110 mm
Digital zoom : 24x
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1

Fixed focal length : 4 mm
Flip & mirror : Y
Focus : Manual
Fog proof : Y
Form factor : Dome
Frame rate : 60 fps
Height : 90 mm
Highlight Compensation (HLC) : Y
Housing material : Metal
IK code : IK08
Image quality adjustment : Contrast
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
Intelligent Video Surveillance (IVS) system features : Crossing line, Defocus, Face detection, Missing object, People counting
LED type : IR
Lens viewing angle, diagonal : 104.8°
Lens viewing angle, horizontal : 88.6°
Lens viewing angle, vertical : 47.5°
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum aperture number : 1.4
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Microphone in : Y
Minimum illumination : 0.015 lx
Mounting type : Ceiling
Networking standards : IEEE 802.3af
Night vision : Y
Night vision distance : 30 m
Noise reduction : Y
Noise reduction technology : 3D noise reduction
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of lenses : 1
Number of sensors : 1
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 354°
Placement supported : Indoor & outdoor
Power consumption (Power over Ethernet (PoE)) : 9 W
Power consumption (typical) : 8 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Ivory
Progressive scan : Y
Protection features : Vandal proof
PTZ control : Y
PTZ modes : Digital PTZ
Quality of Service (QoS) support : Y
Remote viewing : Y
Sample rate : 48 kHz
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage temperature (T-T) : -50 - 60 °C

Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Tilt angle range : 0 - 67°
Total megapixels : 2.16 MP
USB port : Y
Video formats supported : AVC, H.264, H.265, MPEG4
Video motion detection : Y
Video streaming : Y
Web browser : Y
Weight : 380 g
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y
Width : 110 mm
Windows operating systems supported : Windows 10, Windows 7, Windows 8.1
Zoom capability : Y