

# USB VGA to Cat5e/6 KVM Adapter Cable (CPU Module) - KA7170 VGA/USB 50m



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : KA7174-AX-G

Built-in display : N

Compatibility : KN2116VA,KN2132VA,KN4116VA,KN4132VA,KN4164V,2L-5301UP,KN8132V,2L-5302UP,KN8164V,2L-5303UP,KN2124VA,KN2140VA,KN4124VA,KN4140VA,VE-RMK1U,KN1132V,2XRT-0015G,KA7171AK

Country of origin : Taiwan

DC input voltage : 5 V

DC-in jack : Y

Depth : 203 mm

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Harmonized System (HS) code : 85176200

HD type : WUXGA

Height : 25 mm

Housing material : Metal

I/O ports : 1 x SPHD, 1 x 6-pin Mini-DIN, 1 x USB Type A

LED indicators : Y

Master (outer) case gross weight : 5.61 kg

Master (outer) case height : 194 mm

Master (outer) case length : 336 mm

Master (outer) case volume : 19538.62 cm<sup>3</sup>

Master (outer) case width : 300 mm

Maximum resolution : 1920 x 1200 pixels

Operating relative humidity (H-H) : 0 - 95%

Operating temperature (T-T) : 0 - 50 °C

Package depth : 283 mm

Package height : 173 mm

Package type : Box
Package volume : 3114.85 cm <sup>3</sup>
Package weight : 1.02 kg
Package width : 62 mm
Packaging content : 1x KA7174 KVM Adapter Module with USB, PS/2, and RS-232 Local Console 1x power adapter 1x KVM cable (VGA, USB, PS/2) 1x console cable (VGA, USB, PS/2) 1x foot pad set (4pcs) 1x user instructions
Power consumption (typical) : 1.75 W
Product colour : Black
Products per master (outer) case : 5 pc(s)
Push button : Y
Rack mounting : N
Serial port type : DE-9 (DB-9)
Serial ports quantity : 2
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -20 - 60 °C
Video bandwidth : 60 Hz
Weight : 490 g
Width : 86.4 mm