

HANWHA- Camera QNO-7082R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QNO-7082R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Adjustment shutter speed : Auto/Manual
Alarm input/output : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Camera shutter speed : 1/5 - 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12
Detect distance (tele) : 129 m
Detect distance (wide) : 27 m
Diameter : 7.8 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Flip & mirror : Y

Focal length range : 3.2 - 10 mm
Form factor : Bullet
Frame rate : 30 fps
Housing material : Aluminium
Identify distance (tele) : 13 m
Identify distance (wide) : 3 m
IK code : IK10
Infrared (IR) cut-off filter : Y
Intelligent Video Surveillance (IVS) system features : Defocus
Internal memory : 512 MB
International Protection (IP) code : IP66
IP address filtering : Y
LED type : IR
Length : 259.8 mm
Lens viewing angle, diagonal : 115.7°
Lens viewing angle, horizontal : 98.6°
Lens viewing angle, vertical : 52.3°
Maximum aperture number : 2.9
Maximum memory card size : 128 GB
Maximum resolution : 2560 x 1440 pixels
Minimum aperture number : 1.6
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Night vision : Y
Night vision distance : 30 m
Noise reduction : Y
Number of cameras : 1
Number of sensors : 1
Observe distance (tele) : 52 m
Observe distance (wide) : 11 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Optical zoom : 3.1x
Placement supported : Outdoor
Power consumption (max) : 9.6 W
Power consumption (Power over Ethernet (PoE)) : 11.4 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Grey
Quality of Service (QoS) support : Y
Recognize distance (tele) : 26 m
Recognize distance (wide) : 6 m
Sample rate : 8 kHz
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -40 - 60 °C
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP
Total megapixels : 4 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y

Voice codecs : G.711, G.711ulaw, G.726
Weight : 900 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N