



DESCRIPTION

Brothers TD4650TNWB Thermal Transfer Label and Receipt printer provides the media flexibility, longevity and cost efficiency required for high volume printing at 203dpi resolution. With support for ZPL II emulation and a variety of additional printer command languages, developers can easily integrate printing into existing legacy systems.

High quality thermal transfer printing

The 300dpi print resolution produces incredibly crisp, easy-to-read text and barcodes using thermal transfer ink ribbons and media. As your printing needs change, so too can the Brother TD4750TNWB label printer.

High capacity thermal transfer print ribbons in various materials depending on application

Large capacity ribbons of up to 300 metres can be installed, and are available in wax for standard paper media, wax/resin for improved resistance to chemicals on paper and synthetic media or resin for the best durability against heat and chemicals.

Industry standard printer commands, as standard

Print from Windows using the standard printer driver, or integrate the Brother TD4750TNWB label printer into your legacy systems using ZPL/ZPL2 or EPL printer commands without needing to change your existing software.

Fast print speed and processing to improve efficiency

A fast print speed of 152.4mm/second means less time waiting for your labels to print and more time being productive.

Connectivity to suit your requirements

With integrated USB, Ethernet, Serial ports, Bluetooth and WiFi as standard, the Brother TD4750TNWB will have no problems connecting to your existing equipment and infrastructure.

Optional accessories to further improve productivity

Add a durable label cutter, automatic label peeler or external roll holder for larger capacity rolls to further enhance your efficiency and provide maximum printer up-time.

TECHNICAL CHARACTERISTICS

Brand : BROTHER

Part number : TD-4650TNWB

Connectivité :

Bluetooth : Y
Bluetooth version : 4.2
Built-in barcodes : AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Code-128 Codabar Library, EAN128, EAN13, EAN8, GS1 DataBar, ITF-14, Interleaved 2/5, MaxiCode, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E
Bundled software : Bartender Ultra Lite Edition
Cables included : AC, USB
Colour : N
Colour display : Y
Connectivity technology : Wired & Wireless
Control type : Buttons
Depth : 285 mm
Display : LCD
Display diagonal : 5.84 cm (2.3»)
Ethernet LAN : Y
Flash memory : 128 MB
Harmonized System (HS) code : 84433210
Height : 191 mm
Internal memory : 128 MB
Linux operating systems supported : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Maximum label width : 11.2 cm
Maximum printing width : 10.8 cm
Maximum resolution : 203 x 203 DPI
Maximum roll diameter : 12.7 cm
Operating relative humidity (H-H) : 5 - 40%
Operating temperature (T-T) : -40 - 60 °C
Print speed : 203.2 mm/sec
Print technology : Direct thermal / Thermal transfer
Product colour : Black
RS-232 ports : 1
Server operating systems supported : Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Storage relative humidity (H-H) : 25 - 85%
Storage temperature (T-T) : 10 - 90 °C
USB 2:0 ports quantity : 1
USB port : Y
Weight : 3 kg
Width : 219 mm
Wi-Fi : Y
Wi-Fi standards : 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Windows operating systems supported : Windows 10, Windows 7, Windows 8, Windows 8.1