

HANWHA IP camera XNB-6001



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XNB-6001

Représentation / réalisation :

Type : IP security camera

Active tampering alarm : Y

Alarm input/output : Y

Alert notification type : E-mail

Anti-flicker : Y

Audio detection : Y

Audio formats supported : AAC-LC, ADPCM, G.711, G.726

Audio system : 2-way

Auto-tracking : Y

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)

Camera shutter speed : 2 - 1/12000 s

Camera shutter type : Electronic

Card reader integrated : Y

Compatible memory cards : SD, SDHC, SDXC

Composite video out : 1

Connectivity technology : Wired

Day/night mode : Y

Depth : 131.1 mm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Flip & mirror : Y

Fog proof : Y

Frame rate : 60 fps
Height : 28 mm
Highlight Compensation (HLC) : Y
Image quality adjustment : Contrast
Image stabilizer : Y
Intelligent Video Surveillance (IVS) system features : Face detection
IP address filtering : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum memory card size : 256 GB
Maximum resolution : 1920 x 1080 pixels
Microphone in : Y
Networking standards : IEEE 802.3af
Noise reduction : Y
Noise reduction technology : 3D noise reduction
Number of cameras : 1
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -10 - 55 °C
People counting function : Y
Placement supported : Indoor
Power consumption (max) : 6.5 W
Power consumption (Power over Ethernet (PoE)) : 6 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Ivory
PTZ control : Y
PTZ modes : Digital PTZ
Quality of Service (QoS) support : Y
Remote viewing : Y
Sample rate : 16 kHz
Security algorithms : 802.1x RADIUS, EAP-TLS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -30 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3 (MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Text caption overlay : Y
Total megapixels : 2 MP
USB port : Y
Video compression formats : AVC, H.264, H.265, M-JPEG, MPEG4
Web browser : Y
Weight : 245 g
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y
Width : 86 mm
Windows operating systems supported : Windows 10, Windows 7, Windows 8.1