

Aten CE624 extender kit dvi/usb hdbaset 2.0 150M



DESCRIPTION

The ATEN CE620 USB DVI HDBaseT+ 2.0 KVM Extender integrates the latest HDBaseT+ 2.0 technologies to provide the most reliable transmission of video, audio, USB and RS-232 signals available on the market.

The CE620 delivers high-quality DVI video, PCM 2-channel digital audio, USB 2.0 and RS-232 signals up to 100 meters from the source computer using a single Cat5e/6 cable.

With a simple cable installation supporting various signals, the CE620 is ideal for applications where convenient remote access is required - in places such as transportation control centers, medical facilities, industrial warehouses and extended workstations.

Features :

HDBaseT+ 2.0 connectivity technology

- Extends video, audio, USB and RS-232 signals via a single Ethernet cable
- EDID Buffer for smooth power-up and the highest quality display
- Enhanced bit error detection and correction to resist signal interference during high-quality video transmissions

Long distance superior video quality

- HDBaseT+ Standard mode up to 1920 x 1200 @ 100 m
- HDBaseT+ Long Reach mode up to 1920 x 1080 @ 150 m

Long Reach mode switch + switches between HDBaseT+ Standard and Long Reach modes in a snap

Integrated USB 2.0 ports + ensuring fast transmission speeds for peripherals

Supports 2-channel PCM digital audio + ensuring highquality audio transmissions

Supports PC Wakeup function via pushbutton or hotkey

Built-in 8KV/15KV ESD protection (Contact voltage 8KV; Air voltage 15KV)

Note: The CE620 does not support HDCP.

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : CE924-AT-G

Caractéristiques :

Type : Transmitter & receiver

AC adapter included : Y

Cables included : DisplayPort, USB Type-A to USB Type-B

Connectivity technology : Wired
Harmonized System (HS) code : 84733080
LED indicators : Y
Master (outer) case gross weight : 4.28 kg
Master (outer) case height : 153 mm
Master (outer) case length : 556 mm
Master (outer) case net weight : 3.08 kg
Master (outer) case width : 247 mm
Material : Metal
Maximum digital resolution : 4096 x 2160 pixels
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 540 mm
Package height : 233 mm
Package weight : 4.04 kg
Package width : 131 mm
Product colour : Black
Products per master (outer) case : 1 pc(s)
Receiver depth : 17.4 cm
Receiver height : 2.88 cm
Receiver local video port type : DisplayPort
Receiver weight : 850 g
Receiver width : 15.6 cm
RJ-45 ports quantity (receiver) : 1
RJ-45 ports quantity (transmitter) : 1
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
Transmitter depth : 17.4 cm
Transmitter height : 2.88 cm
Transmitter video port type : DisplayPort
Transmitter weight : 820 g
Transmitter width : 15.4 cm
USB port type : USB Type-A
Weight : 3.08 kg