

BOSCH NIN-73023-A10AS



DESCRIPTION

This camera provides clear images 24/7 even at night or under low-light conditions.

The exceptional starlight sensitivity enables this camera to work with a minimum of ambient light. The extended dynamic mode provides detailed images in scenes with challenging lighting.

The camera is available in 1080p or 720p resolution versions and provides up to 60 images per second.

The aesthetic vandal-resistant housing makes the camera suitable for indoor or outdoor installation.

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NIN-73023-A10AS

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

BNC output ports : 1

Built-in HDD : N

Camera pan control : Y

Camera tilt control : Y

Card reader integrated : Y

Compatible memory cards : MicroSDHC, MicroSDXC

Connectivity technology : Wired

DC output voltage : 12

Diameter : 15.8 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Focal length range : 10 - 23 mm

Focus : Motorized

Form factor : Dome

Height : 124 mm

Housing material : Aluminium
IK code : IK10
International Protection (IP) code : IP66
Maximum memory card size : 2000 GB
Maximum resolution : 1920 x 1080 pixels
Mounting type : Ceiling
Networking standards : IEEE 802.1x, IEEE 802.3af
Number of cameras : 1
Number of effective pixels (H x V) : 1280 x 720 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 5 - 93%
Operating temperature (T-T) : -30 - 50 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 360°
Placement supported : Outdoor
Power consumption (max) : 7.2 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Black, White
Quality of Service (QoS) support : Y
Security algorithms : 3DES, DES, MD5, SHA-1, SHA-256, SSL/TLS, TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 98%
Storage temperature (T-T) : -50 - 70 °C
Supported network protocols : SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS, IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/ RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA
Supported video modes : 1080p
Tilt angle range : 0 - 90°
Total megapixels : 2 MP
Video compression formats : H.264, M-JPEG
Web browser : Y
Web-based management : Y
Wi-Fi : N
Zoom capability : Y