

HANWHA- Thermal Camera TNO-3050T



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : TNO-3050T
Représentation / réalisation :
Type : IP security camera
AC input voltage : 24 V
Active tampering alarm : Y
Alert notification type : E-mail
Angle of rotation : 270°
Audio formats supported : AAC-LC, G.711, G.711 -law, G.726
Built-in microphone : Y
Camera pixel size : 12 µm
Compatible memory cards : MicroSD (TransFlash), SDHC, SDXC
Connectivity technology : Wired
DC output voltage : 12
Depth : 401.3 mm
Detect distance : 15 m
Digest authentication : Y
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Fixed focal length : 3.5 cm
Flash memory : 256 MB
Form factor : Bullet
Housing material : Aluminium
HTTPS encryption : Y
Internal memory : 1024 MB
International Protection (IP) code : IP66
IP address filtering : Y

Languages support : Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Polish, Portuguese, Russian, Swedish, Turkish
Lens viewing angle, diagonal : 7.8°
Lens viewing angle, horizontal : 6.3°
Lens viewing angle, vertical : 4.7°
Maximum memory card size : 256 GB
Maximum resolution : 320 x 240 pixels
Motion sensor : Y
Mounting type : Wall
Number of cameras : 1
Number of languages : 15
Number of lenses : 1
Number of users : 20 user(s)
Operating temperature (T-T) : -40 - 60 °C
Password protection type : User
Placement supported : Outdoor
Power consumption (Power over Ethernet (PoE)) : 7.5 W
Power source type : AC, DC, PoE
Privacy masking : Y
Product colour : White
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS, SSL/TLS
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Temperature sensor : Y
Thermal sensitivity (NETD) : 60 mK
User access level : User
Video compression formats : H.264, H.265, M-JPEG
Video formats supported : H.264, H.265
Weight : 2.74 kg
Width : 147.5 mm
Zoom capability : Y