

HANWHA- 2MP Analog Vandal-Resistant Dome Camera HCV-6080



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : HCV-6080
Représentation / réalisation :
Type : CCTV security camera
Réseau :
Bluetooth : N
Certification : CE
AC input voltage : 24 V
Alarm input/output : Y
Analog signal format system : PAL
Angle of rotation : 355°
Back Light Compensation (BLC) : Y
BNC output ports : 1
Built-in HDD : N
Camera pan control : Y
Camera shutter speed : 1 - 1/12000 s
Camera shutter type : Electronic
Camera tilt control : Y
Closest focusing distance : 0.5 m
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12
Diameter : 13.7 cm
Ethernet LAN : N
Focal length range : 3.2 - 10 mm
Form factor : Dome
Frame rate : 25 fps

Height : 106.1 mm
Highlight Compensation (HLC) : Y
Housing material : Aluminium
IK code : IK10
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP66
Lens viewing angle, diagonal : 128.4°
Lens viewing angle, horizontal : 110.2°
Lens viewing angle, vertical : 55.4°
Maximum aperture number : 1.6
Maximum operating distance : 500 m
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.01 lx
Mounting type : Ceiling/wall
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 350°
Placement supported : Outdoor
Power consumption (max) : 4.8 W
Power source type : AC, DC
Privacy masking : Y
Product colour : Ivory
Sensor type : CMOS
Tilt angle range : 0 - 67°
Total megapixels : 2 MP
Video motion detection : Y
Weight : 718 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N