

HANWHA- IP Camera XNV-6081R



DESCRIPTION

The most powerful chipset WISENET 5

Wisenet X series is supercharged by the most powerful chipset ever incorporated into a full camera range. The Wisenet 5 chip uses an all-new architecture that enables faster processing. That means you get the best video performance just as you need it.

Easy installation with modular structure and motorized PTRZ

Wisenet X PLUS cameras offer easy installation with their modular structure and motorized PTRZ. The product package has been renewed to save time and money in installation and maintenance.

Extended tilt range for greater flexibility

Extended tilt angle has been added for greater flexibility in placement and use cases of Wisenet X PLUS cameras.

Advanced DIS and shock detection with built-in gyro sensors

Wisenet X PLUS cameras have built-in gyro sensors to enable advanced DIS with reduced motion blur and shock detection which detects when the camera is hit.

High reliability in challenging environments

One of the most important features of a security camera is reliability in challenging environments. Wisenet X PLUS cameras offer high reliability by providing resistance to weather and impact with IP67, IP66, IP6K9K, and IK10+ ratings.

Audio playback on event

Audio playback feature responds to user-defined events to assist operators communicate with the public.

Optional accessories for various applications

A weather cap and the skin covers available in black and ivory would blend in with the surroundings of different kinds.

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XNV-6081R

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N
Angle of rotation : 355°
Built-in HDD : N
Camera pan control : Y
Camera shutter speed : 1/12000 s
Camera tilt control : Y
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), SDHC, SDXC
Connectivity technology : Wired
DC output voltage : 12
Diameter : 18 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Form factor : Dome
Frame rate : 60 fps
Height : 125 mm
Housing material : Aluminium
IK code : IK10+
Internal memory : 1024 MB
International Protection (IP) code : IP66, IP67, IP69K
Maximum aperture number : 3.6
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.4
Mounting type : Ceiling
Night vision : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -50 - 60 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 360°
Placement supported : Indoor & outdoor
Power consumption (max) : 13.3 W
Power consumption (Power over Ethernet (PoE)) : 10.3 W
Power consumption (typical) : 10.4 W
Power source type : DC, PoE
Product colour : White
PTZ control : Y
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Tilt angle range : -45 - 85°
Total megapixels : 2 MP
USB port : Y
Video compression formats : H.264, H.265, M-JPEG

Weight : 1.75 kg

Wi-Fi : N