

EPDU MA 0U (309 32A 1P)28XC13:4XC19



DESCRIPTION

Switch and meter outlets & IT equipment across A and B feed: Combines both Switched and Metered Outlet functionality together in 1 ePDU

ePDU G3 Managed models allow complete lights-out control and metering of devices including devices powered across multiple ePDUs. They include IEC Class 1 ($\pm 1\%$) billing grade accuracy, an advanced hot-swap meter with LCD pixel display showing V, W, A and kWh, and the ability to daisy chain 8 ePDUs to share the same network connection and IP address.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMAB71

Design :

Type : Single-phase

Caractéristiques :

Certification : CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011\nEN 61000-6-2:2005\nEN 50581 : 2012, REACH, WEEE\nISO 9001:2008 / ISO 14001:2004

AC input frequency : 50 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 32 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 53 mm

Dimensions (WxDxH) : 52 x 53 x 1829 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 1829 mm

LED indicators : Y

Management protocols : SNMP, Telnet

| |
|--|
| Maximum current : 32 A |
| Maximum input current per phase : 32 A |
| Maximum power : 7400 W |
| Monitoring : Voltage |
| Mounting : Vertical |
| Nominal input voltage : 230 V |
| Nominal output voltage : 230 V |
| Operating temperature (T-T) : 0 - 60 °C |
| Output connections : 28 x C13 & 4 x C19 |
| Package depth : 214 mm |
| Package height : 1955 mm |
| Package width : 200 mm |
| PDU types : Managed |
| Power plug : IEC 60309 |
| Product colour : Black |
| Rack capacity : 0U |
| Rack mount kit : Y |
| Rack mounting : Y |
| Serial ports quantity : 1 |
| Supported network protocols : HTTP, HTTPS, SSL, FTP, SMTP, DNS, DHCP, LDAP, RADIUS |
| Sustainability certificates : RoHS |
| Weight : 6.3 kg |
| Width : 52 mm |