

LEGRAND UPS Daker DK Plus 5000 VA without batteries



DESCRIPTION

Daker DK UPS Plus is a single phase uninterruptible power supply with high frequency PWM technology, Double Conversion OnLine.

It delivers a rated power of 1000-2000-3000-5000-6000-10000VA, equipped with valve-regulated, hermetically-sealed accumulator batteries, contained in a specific compartment inside the UPS or in one or more external cabinets.

With the reversible screen, the Daker DK Plus UPS can be used in both tower and 19» rack configuration.

TECHNICAL CHARACTERISTICS

Brand : LEGRAND
Part number : 310175
Design :
Certification : EN 62040-1, EN 62040-2, EN 62040-3
AC outlet types : Hardwire
AC outlets quantity : 1 AC outlet(s)
Auto shut-off : N
Crest factor : 3:1
Depth : 680 mm
Detachable power cord : Y
Display type : LCD
Efficiency : 94%
Efficiency (ECO mode) : 97%
Emergency Power Off (EPO) : Y
Form factor : Rackmount
Height : 440 mm
Input current Total Harmonic Distortion (THD) : 3%
Input frequency : 47/63 Hz
Input operation voltage (max) : 280 V
Input operation voltage (min) : 176 V
Input power factor : 0.99
International Protection (IP) code : IP20

LED indicators : Status
Management protocols : Network management,Simple Network Management Protocol (SNMP)
Master (outer) case gross weight : 19.4 kg
Master (outer) case height : 316 mm
Master (outer) case length : 872 mm
Master (outer) case width : 560 mm
Noise level : 50 dB
Number of input phases : 1
Number of output phases : 1
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 232 V
Output operation voltage (min) : 228 V
Output power : 5000 W
Output power capacity : 5 kVA
Output power factor : 1
Output voltage regulation : 1%
Output voltage Total Harmonic Distortion (THD) : 3%
Package depth : 26.3 mm
Package height : 440 mm
Package weight : 18.5 kg
Package width : 88 mm
Pallet net height : 152 cm
Pallet net length : 100 cm
Pallet net weight : 233.4 kg
Pallet net width : 120 cm
Potential-free output : N
Power factor : 1
Power plug : Hardwire
Power source type : AC
Product colour : Black
Products per master (outer) case : 1 pc(s)
Products per pallet : 12 pc(s)
Rack capacity : 2U
Serial interface : Y
Serial interface type : RS-232
Surge energy rating : 1900 J
UPS topology : Double-conversion (Online)
USB port : Y
Waveform : Sine
Weight : 25 kg
Width : 88 mm