

SONY- 4000 Lm projector VPL-CH355



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand :	SONY
Part number :	VPL-CH355
Réseau :	
Smart TV :	N
Caractéristiques :	
HDCP :	Y
Vidéo :	
Full HD :	Y
AC (power) in :	Y
AC input frequency :	50 - 60 Hz
AC input voltage :	100 - 240 V
Analog signal format system :	NTSC 3.58, NTSC 4.43, PAL, PAL M, PAL N, SECAM
Audio (L/R) in :	1
Built-in display :	N
Built-in speaker(s) :	Y
Card reader integrated :	N
Composite video in :	1
Contrast ratio (typical) :	2500:1
Depth :	330.5 mm
DVI port :	N
Ethernet LAN :	Y
Ethernet LAN (RJ-45) ports :	1
Focus :	Manual
HDMI ports quantity :	1
Heat dissipation :	1204 BTU/h
Height :	113 mm
Horizontal lens shift range :	-4 - 4%

Horizontal scan range : 19 - 92 kHz
Keystone correction, horizontal : -20 - 20°
Keystone correction, vertical : -30 - 30°
Lamp power : 250 W
Light source type : Lamp
Manual : Y
Market positioning : Home cinema
Native aspect ratio : 16:10
Noise level (economic mode) : 29 dB
Number of built-in speakers : 1
On Screen Display (OSD) : Y
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese
Operating relative humidity (H-H) : 20 - 80%
Operating temperature (T-T) : 0 - 40 °C
Placement : Desktop
Power consumption (max) : 353 W
Power consumption (network standby) : 6.3 W
Power consumption (PowerSave) : 254 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 272 W
Power source : AC
Product colour : White
Product type : Standard throw projector
Projection distance : 1.02 - 7.62 m
Projection technology : 3LCD
Projector brightness : 4000 ANSI lumens
Projector brightness (economic mode) : 2600 ANSI lumens
Projector native resolution : WUXGA (1920x1200)
Remote control included : Y
RMS rated power : 12 W
RS-232 ports : 1
Screen size compatibility : 1016 - 7620 mm (40 - 300»)
Serial interface type : RS-232
Service life of light source : 4000 h
Service life of light source (economic mode) : 5000 h
Storage relative humidity (H-H) : 20 - 80%
Storage temperature (T-T) : -20 - 60 °C
Supported aspect ratios : 16:10
Supported video modes : 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
S-Video inputs quantity : 1
Throw ratio : 1.5 - 2.2:1
USB 2.0 ports quantity : 2
Vertical lens shift range : -5 - 5%
Vertical scan range : 48 - 92 Hz
VGA (D-Sub) ports quantity : 3
Warranty card : Y
Weight : 5.7 kg
Width : 406 mm
Zoom capability : Y
Zoom ratio : 1.45:1
Zoom type : Manual