



DESCRIPTION

Designed to provide surface-mount bass augmentation for new and existing background music systems. Features one 5.25» (133 mm) woofer that delivers deep bass down to 40 Hz without audible distortion.

- Low-frequency loudspeaker featuring one 5.25» (133mm) woofer that delivers deep, non-localized bass down to 40 Hz without audible distortion. For surface-mount applications
- Acoustimass speaker technology filters out audible distortion to deliver non-localized bass
- Designed to work with the FreeSpace 3 surface and flush satellite speakers, or existing systems where additional bass reinforcement is desired
- Module design allows parallel connection of multiple bass modules and can accommodate two or four FreeSpace 3 satellites per bass module
- Selectable 70/100V or low impedance

Applications

- Retail stores
- Restaurants and bars
- Lobbies and conference rooms

TECHNICAL CHARACTERISTICS

Brand : BOSE

Part number : 40145

Certificat :

Certification : CE

AC input voltage : 70/100 V

Impedance : 5

Material : PVC

Number of subwoofers : 1

Package weight : 11.3 kg

Power consumption (typical) : 200 W

Product colour : White

Subwoofer depth : 34.2 cm

Subwoofer driver diameter : 13.3 cm

Subwoofer driver diameter (imperial) : 13.3 cm (5.25«)

Subwoofer frequency range : 40 - 315 Hz

Subwoofer height : 35.6 cm

Subwoofer peak power : 800 W

Subwoofer sensitivity : 96 dB

Subwoofer weight : 7.9 kg

Subwoofer width : 19.1 cm