

LEGRAND UPS Keor SP 2000 VA, IEC sockets



DESCRIPTION

The Keor SP is a single phase uninterruptible power supply with line interactive technology. It delivers a rated power of 600-800-1000-1500-2000VA, it is CPU-controlled and is equipped, internally, with valve-regulated, hermetically sealed lead accumulator batteries.

The presence of an electronic stabilizer (AVR) inside the UPS provides the connected loads with effective protection against any interference in the electrical mains.

TECHNICAL CHARACTERISTICS

Brand : LEGRAND
Part number : 310192
Design :
Certification : EN 62040-1, EN 62040-2
AC outlet types : C13 coupler
AC outlets quantity : 6 AC outlet(s)
Audible alarm(s) : Y
Auto shut-off : N
Automatic Voltage Regulation (AVR) : Y
Battery capacity : 9 Ah
Battery technology : Sealed Lead Acid (VRLA)
Depth : 380 mm
Efficiency : 97%
Form factor : Mini Tower
Harmonized System (HS) code : 85078000
Height : 173 mm
Input frequency : 45/65 Hz
Input operation voltage (max) : 280 V
Input operation voltage (min) : 170 V
LED indicators : Y
Master (outer) case gross weight : 12.4 kg
Master (outer) case height : 265 mm

Master (outer) case length : 465 mm
Master (outer) case width : 243 mm
Noise level : 40 dB
Number of batteries supported : 2
Number of input phases : 1
Number of output phases : 1
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output frequency regulation : 1 Hz
Output operation voltage (max) : 253 V
Output operation voltage (min) : 207 V
Output power : 1200 W
Output power capacity : 2 kVA
Output power factor : 0.6
Output voltage regulation : 10%
Package depth : 9.73 mm
Package height : 173 mm
Package weight : 11.8 kg
Package width : 148 mm
Pallet net height : 95 cm
Pallet net length : 100 cm
Pallet net weight : 373.4 kg
Pallet net width : 120 cm
Potential-free output : N
Power plug : C14 coupler
Power protection features : Overcharge, Overdischarge, Overload, Short circuit
Power source type : AC
Product colour : Black, White
Products per master (outer) case : 1 pc(s)
Products per pallet : 30 pc(s)
Serial interface : Y
Surge protection : Y
Sustainability certificates : CE
Sustainability compliance : Y
UPS topology : Line-Interactive
USB 2:0 ports quantity : 2
USB port : Y
USB port type : USB Type-A/USB Type-B
Waveform : Sine
Weight : 11.8 kg
Width : 148 mm