



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK

Part number : TL-SG1210MP

Réseau :

Auto MDI/MDI-X : Y

Design :

Certification : CE, FCC

10G support : N

Auto-negotiation : Y

Basic switching RJ-45 Ethernet ports quantity : 9

Basic switching RJ-45 Ethernet ports type : Gigabit Ethernet (10/100/1000)

Cable types supported : Cat3, Cat4, Cat5, Cat5e

Combo SFP ports quantity : 1

Copper ethernet cabling technology : 10BASE-T, 100BASE-TX

Depth : 209 mm

Fanless : Y

Flow control support : Y

Harmonized System (HS) code : 85176990

Heat dissipation : 482.17 BTU/h

Height : 26 mm

LED indicators : Y

MAC address auto-aging supported : Y

MAC address auto-learning supported : Y

MAC address table : 4000 entries

Networking standards : IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z

Operating relative humidity (H-H) : 10 - 90%

Operating temperature (T-T) : 0 - 40 °C

Power consumption (max) : 141.4 W

Power over Ethernet (PoE) : Y
Power over Ethernet (PoE) power per port : 30 W
Power over Ethernet plus (PoE+) ports quantity : 8
Product colour : Black
Rack mounting : N
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Store-and-forward : Y
Switch type : Unmanaged
Switching capacity : 20 Gbit/s
Total Power over Ethernet (PoE) budget : 123 W
Width : 126 mm