

N300 wireless poe ceiling/wall mount access point



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : EAP115
Caractéristiques :
5 GHz : N
Design :
Certification : CE, FCC, RoHS
2:4 GHz : Y
AC adapter included : Y
Access Control List (ACL) : Y
Antenna gain level (max) : 4 dBi
Antenna type : Internal
Antennas quantity : 2
Automatic channel selection : Y
Depth : 189.4 mm
Ethernet LAN (RJ-45) ports : 1
Ethernet LAN data rates : 10,100,1000 Mbit/s
Frequency band : 2.4 - 2.4835 GHz
Harmonized System (HS) code : 85176990
Height : 29.5 mm
LED indicators : Y
MAC address filtering : Y
Maximum data transfer rate : 300 Mbit/s
Maximum data transfer rate (2:4 GHz) : 300 Mbit/s
Mounting kit : Y
Networking standards : IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Number of products included : 1 pc(s)
Number of SSID supported : 8

On/off switch : Y
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output current : 0.6 A
Output voltage : 9 V
Placement : Ceiling, Wall
Power consumption (typical) : 2.8 W
Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Rate limiting : Y
Receiver sensitivity : 300M: -71dBm@10% PER 150M: -75dBm@10% PER 54M: -78dBm@10% PER 11M: -93dBm@8% PER 6M: -92dBm@10% PER 1M: -96dBm@8% PER
Reset button : Y
Security algorithms : 64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SSH, WPA, WPA-PSK, WPA2-Enterprise, WPA2-PSK
Service Set Identifier (SSID) features : Hidden SSID
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
System status alarm : Y
WAN connection : Ethernet (RJ-45), Wi-Fi
Web-based management : Y
Width : 172.3 mm