

BOSCH NIN-70122-F0A



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NIN-70122-F0A

Représentation / réalisation :

Type : IP security camera

Audio formats supported : AAC, G.711

Built-in microphone : Y

Cabling technology : 10/100Base-T(X)

Camera shutter type : Electronic

Card reader integrated : Y

Compatible memory cards : SDHC, SDXC

Day/night mode : Y

Depth : 33 mm

Detection angle : 180°

Ethernet LAN : Y

Fixed focal length : 2.1 mm

Form factor : Dome

Image quality adjustment : Brightness, Contrast, Saturation

Infrared (IR) cut-off filter : Y

LED type : IR

Lens viewing angle, horizontal : 180°

Lens viewing angle, vertical : 180°

Maximum resolution : 3640 x 2160 pixels

Minimum illumination : 0.18 lx

Motion sensor : Y

Mounting type : Wall

Networking standards : IEEE 802.1x

Night vision : Y

Noise reduction : Y
Operating relative humidity (H-H) : 20 - 93%
Operating temperature (T-T) : -20 - 40 °C
Optical sensor size : 25.4 / 2.3 mm (1 / 2.3»)
Power over Ethernet (PoE) : Y
Power source type : PoE
Privacy protection : Y
Product colour : White
Progressive scan : Y
PTZ control : Y
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 0 - 98%
Supported graphics resolutions : 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, Telnet, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP
Supported video modes : 720p, 1080p
Total megapixels : 12 MP
Video compression formats : H.264, M-JPEG
Video formats supported : H.264, M-JPEG
Weight : 445 g
White balance : Auto, Manual
Wide Dynamic Range (WDR) : Y