



DESCRIPTION

Panasonic WV-S4550L / WV-S4550LM captures the highest quality images in even very challenging and dynamic environments. In particular, the image of the person's face or object at the edge of the fisheye is clear with less distortion. Intelligent Auto (iA) monitors scene dynamics and motion to adjust key camera settings automatically in real-time reducing distortion such as motion blur on moving objects. Adopting H.265 Smart Coding technology, bandwidth efficiency is intelligently increased for longer recording and less storage. Out of the box, the camera supports full data encryption streaming and is compliant to FIPS 140-2 Level 1 standards to keep your video secured. *Value in Advanced mode. It depends on the scene.

TECHNICAL CHARACTERISTICS

Brand : PANASONIC
Part number : WV-S4550L
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Vidéo :
Full HD : Y
Connectivité :
Interface : RJ-45
Adjustment shutter speed : Auto
Alarm input/output : Y
Alert notification type : E-mail
Audio codecs : AAC,ADPCM
Back Light Compensation (BLC) : Y
Built-in HDD : N
Cabling technology : 10/100Base-T(X)
Camera shutter speed : 1/30 - 1/100000 s
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y

DC output voltage : 12, 48
Depth : 154 mm
Diameter : 15.4 cm
Digital zoom : 4x
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Fixed focal length : 0.84 mm
Fog proof : Y
Form factor : Dome
Frame rate : 30 fps
Height : 60.3 mm
Highlight Compensation (HLC) : Y
International Protection (IP) code : IP66
Languages support : German, English, Spanish, French, Italian, Japanese, Portuguese, Russian
LED type : IR
Lens viewing angle, horizontal : 186°
Lens viewing angle, vertical : 186°
Maximum aperture number : 2.4
Maximum memory card size : 256 GB
Maximum resolution : 2192 x 2192 pixels
Microphone in : Y
Mobile operating systems supported : Android, iOS
Mounting type : Ceiling
Night vision : Y
Number of cameras : 1
Number of languages : 9
Number of users : 14 user(s)
Operating relative humidity (H-H) : 10 - 100%
Operating temperature (T-T) : -40 - 60 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Placement supported : Outdoor
Power consumption (max) : 10.9 W
Power consumption (Power over Ethernet (PoE)) : 11.5 W
Power over Ethernet (PoE) : Y
Power source type : PoE
Product colour : White
Protection features : Dust resistant, Shock resistant, Water resistant
PTZ control : N
Security algorithms : FIPS 140-2
Sensor type : MOS
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 288 (QVGA), 640 x 360, 640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 960, 1600 x 1200 (UXGA)
Supported network protocols : IPv6 : TCP/IP, UDP/IP, HTTP, HTTPS, FTP, SMTP, DNS, NTP, SNMP, DHCPv6, RTP, MLD, ICMP, ARP, IEEE 802.1X, DiffServ IPv4 : TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTP/RTCP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, UPnP, IGMP, ICMP, ARP, IEEE 802.1X, DiffServ
Total megapixels : 5 MP
Video formats supported : H.264, H.265, MPEG4
Video motion detection : Y
Web-based management : Y
Weight : 870 g
Width : 154 mm
Wi-Fi : N
Zoom capability : Y