



DESCRIPTION

Sustainability is a key component of the RISE Series display lifts. Vogel's offers an endurance tested design of the display lift of over 30,000 cycles. No EPP/EPS is used in the packaging. There is also a reduction of 85% single used plastic in the packaging. This keeps waste streams to a minimum.

Top down assembly allows for a fast installation of Vogel's RISE display lifts. Various pre-assembled components are screw-mounted from above. An integrated cable management system (CIS®) allows for easy concealment of cabling during assembly. And with the ClickLoc system, you hear the certainty of a solid click when attaching the display to the frame. A software development kit is available upon request for software installation before or during setup.

TECHNICAL CHARACTERISTICS

Brand : VOGEL'S
Part number : 7351050
Design :
Certification : TÜV, CE
Depth : 846 mm
Harmonized System (HS) code : 85299097
Height : 1188 mm
Height adjustment : Y
Lifting speed : 50 mm/sec
Maximum distance to floor : 186.7 cm
Maximum screen size : 2.18 m (86»)
Maximum VESA mount : 800 x 600 mm
Maximum weight capacity : 120 kg
Minimum distance to floor : 88.7 cm
Minimum screen size : 165.1 cm (65»)
Minimum VESA mount : 300 x 300 mm
Motorized : Y
Mounting type : Floor
Number of displays supported : 1
Panel mounting interface : 300 x 300,400 x 200,400 x 300,400 x 400,400 x 600,500 x 200,500 x 300,500 x 400,600 x 200,600 x 300,600 x 400,600 x 600,700 x

400,700 x 450,800 x 400,800 x 450,800 x 500,800 x 600

Product colour : Black

Quantity per pack : 1 pc(s)

Screws included : Y

Width : 955 mm