

HANWHA- 2 Mps Network Dome Camera QND-6021



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QND-6021
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Active tampering alarm : Y
Alert notification type : E-mail
Angle of rotation : 355°
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR), Variable Bit Rate (VBR)
Built-in HDD : N
Camera pan control : Y
Camera tilt control : Y
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Connectivity technology : Wired
Day/night mode : Y
Diameter : 9.9 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Fixed focal length : 4 mm
Fixed focus : Y
Flash memory : 256 MB
Form factor : Dome
Frame rate : 30 fps

Height : 56 mm
Housing material : Plastic
IK code : IK08
Intelligent Video Surveillance (IVS) system features : Defocus, People counting
Internal memory : 512 MB
International Protection (IP) code : IP42
IP address filtering : Y
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
Lens viewing angle, diagonal : 104.5°
Lens viewing angle, horizontal : 87.6°
Lens viewing angle, vertical : 46.4°
Mac operating systems supported : Mac OS X 10.12 Sierra, Mac OS X 10.14 Mojave
Maximum aperture number : 1.6
Maximum memory card size : 128 GB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.1 lx
Mounting type : Ceiling
Night vision : N
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1920 x 1080 pixels
Number of languages : 17
Number of users : 6 user(s)
Operating relative humidity (H-H) : 5 - 90%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 350°
Password protection : Y
Password protection type : User
Placement supported : Indoor & outdoor
Power consumption (Power over Ethernet (PoE)) : 4.8 W
Power consumption (typical) : 2.8 W
Power source type : PoE
Privacy masking : Y
Product colour : White
Quality of Service (QoS) support : Y
Security algorithms : EAP-TLS, HTTPS, LEAP, SSL/TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -30 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 640 x 360, 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP
Tilt angle range : 0 - 69°
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video formats supported : H.264, H.265, M-JPEG
Video motion detection : Y
Web-based management : Y
Weight : 145 g
White balance : ATW, AWC, Indoor, Manual, Outdoor

Wide Dynamic Range (WDR) : Y

Wi-Fi : N

Windows operating systems supported : Windows 10, Windows 7, Windows 8, Windows 8.1