

HANWHA- Camera LNO-6072R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : LNO-6072R
Représentation / réalisation :
Type : IP security camera
Plug and Play : Y
Active tampering alarm : Y
Alert notification type : E-mail
Anti-flicker : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Camera pan control : N
Camera shutter type : Electronic
Camera tilt control : N
Card reader integrated : Y
Closest focusing distance : 0.5 m
Compatible memory cards : MicroSD (TransFlash), MicroSDHC
Connectivity technology : Wired
Day/night mode : Y
Depth : 262 mm
Detect distance (tele) : 128.8 m
Detect distance (wide) : 27.4 m
Diameter : 7.8 cm
Dynamic range : 120 dB
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB

Flip & mirror : Y
Focal length range : 3.2 - 10 mm
Focus : Manual
Form factor : Bullet
Frame rate : 30 fps
Housing material : Plastic
HTTPS encryption : Y
Identify distance (tele) : 12.9 m
Identify distance (wide) : 2.7 m
Infrared (IR) cut-off filter : Y
Internal memory : 512 MB
International Protection (IP) code : IP66
IP address filtering : Y
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
LED type : IR
Lens viewing angle, diagonal : 132°
Lens viewing angle, horizontal : 109°
Lens viewing angle, vertical : 57.4°
Mac operating systems supported : Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave
Maximum aperture number : 1.6
Maximum memory card size : 32 GB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.03 lx
Mirror : Y
Mounting type : Ceiling/wall
Networking standards : IEEE 802.3af
Night vision : Y
Night vision distance : 30 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of languages : 15
Number of sensors : 1
Number of users : 6 user(s)
Observe distance (tele) : 51.5 m
Observe distance (wide) : 11 m
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Indoor & outdoor
Power consumption (Power over Ethernet (PoE)) : 6.4 W
Power consumption (typical) : 5 W
Power source type : PoE
Privacy masking : Y
Product colour : Grey
Protection features : Dust resistant, Splash proof
PTZ control : N
Quality of Service (QoS) support : Y
Recognize distance (tele) : 25.8 m
Recognize distance (wide) : 5.5 m
Security algorithms : 802.1x RADIUS, EAP-LEAP, EAP-TLS, HTTPS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%

Storage temperature (T-T) : -30 - 55 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour
Supported video modes : 720p, 1080p
Total megapixels : 2 MP
Video compression formats : H.264, M-JPEG
Video formats supported : H.264, M-JPEG
Video motion detection : Y
Video streaming : Y
Web browser : Y
Weight : 420 g
White balance : ATW, AWC, Indoor, Outdoor
Wide Dynamic Range (WDR) : Y
Width : 78 mm
Windows operating systems supported : Windows 10, Windows 7, Windows 8.1
Zoom capability : Y