

DEXLAN Switch 6P 10/100 with 4 PoE+ 60W



DESCRIPTION

The DEXLAN 6-port PoE+ switch was designed for small CCTV systems. The housing is made of metal and the device is quite silent. It has 4 x RJ-45 PoE+ ports supplying 30 Watts to PoE cameras, or dual-band Wi-Fi hot-spots. The 2 additional RJ-45 ports can be used for Internet access and the connection of a network video recorder.

Product features:

- 4 x 10/100 PoE+ ports 30 W max EndSpan
- 2 x 100 Mbps RJ-45 Uplink ports - 150 m. max.
- Power supply included: 48 V / 60 W
- The power budget can be higher with a 48 V extra power supply plugged to the terminal block
- Includes 2 fixing kits (DIN/wallmount)
- Supported temperature range in operation: -10°C to 60°C
- IP-30 Aluminum housing
- 75 W optional power supply, please order PN 314647

TECHNICAL CHARACTERISTICS

Brand : DEXLAN

Part number : DX1016

Main features :

Network standard : Gigabit

ODI Model Layer : Without

Management : No

Operating environment : SMB

Industrial : No

Rackmount : Yes

PoE function : No

Power supply : Embedded power supply

Outband console port : No

Temperature supported in operation : -10° to 60° C

Mounting system : 19» kit included
Connectors :
Total number of ports : 16
Number of RJ-45 ports : 16
Number of fiber ports : 0
Number of BNC Ethernet ports : 0
Other ports : No
RJ-45 patch cords :
Number of 10/100 ports : 0
Number of 10G ports : 0
Number of Gigabit ports : 16
Fiber optics :
Number of 100FX ports : 0
Number of SFP Gigabit ports : 0
Number of SFP+ ports : 0
Number of SFP 1G/100 ports : 0
Number of SFP 100FX ports : 0
PoE data :
PoE standard : -
PoE budget (Watts) : 0
Number of 15-Watt PoE ports : 0
Number of 30-Watt PoE+ ports : 0
Number of 60-W PoE++ ports : 0
Dimensions :
Length (mm) : 280
Width (mm) : 180
Height (mm) : 44