

HANWHA- Camera PNM-C7083RVD



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand :	HANWHA
Part number :	PNM-C7083RVD
Représentation / réalisation :	
Type :	IP security camera
Réseau :	
Bluetooth :	No
Angle of rotation :	180°
Back Light Compensation (BLC) :	Yes
Bit rate control :	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD :	No
Camera shutter speed :	1/5 ~ 1/12000 s
Camera shutter type :	Electronic
Card reader integrated :	Yes
Closest focusing distance :	0.5 m
Compatible memory cards :	MicroSD (TransFlash), SDHC, SDXC
Connectivity technology :	Wired
Day/night mode :	Yes
Depth :	135 mm
Detect distance (tele) :	71.8 m
Detect distance (wide) :	28.4 m
Ethernet interface type :	Gigabit Ethernet
Ethernet LAN :	Yes
Ethernet LAN (RJ-45) ports :	1
Flash memory :	512 MB
Flip & mirror :	Yes
Focal length range :	3 - 6 mm
Form factor :	Dome

Height : 93.2 mm
Housing material : Aluminium
Identify distance (tele) : 7.2 m
Identify distance (wide) : 2.8 m
IK code : IK10
International Protection (IP) code : IP66
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 2.2
Mounting type : Ceiling
Night vision : Yes
Night vision distance : 25 m
Noise reduction : Yes
Noise reduction technology : Smart Super Noise Reduction (SSNR)
Number of cameras : 2
Observe distance (tele) : 28.7 m
Observe distance (wide) : 11.4 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 355°
Placement supported : Indoor & outdoor
Power consumption (max) : 20 W
Power consumption (Power over Ethernet (PoE)) : 15.5 W
Power source type : PoE
Privacy masking : Yes
Product colour : White
RAM capacity : 2048 MB
Recognize distance (tele) : 14.4 m
Recognize distance (wide) : 5.7 m
Security algorithms : EAP-LEAP, EAP-PEAP, EAP-TLS, MSCHAPv2
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)
Tilt angle range : 0 - 78°
Total megapixels : 2 MP
USB port : Yes
Video compression formats : H.264, H.265, M-JPEG
Weight : 1.33 kg
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Yes
Width : 215 mm
Wi-Fi : No