

19" Dual Rail LCD console 16-Port KVM Switch USB - PS/2 VGA



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : CL5816N-ATA-FG

AC input frequency : 50 - 60 Hz

AC input voltage : 100-240 V

Built-in display : Y

Console ports : USB A, VGA (D-Sub)

Daisy chain : Y

DDC2B support : Y

Depth : 480 mm

Display : LCD

Display diagonal : 48.3 cm (19")

Harmonized System (HS) code : 85176200

HD type : WUXGA

Height : 44 mm

Hot-swap : Y

Housing material : Metal, Plastic

Input current : 1 A

Keyboard port type : USB, PS/2

LED indicators : Y

Linux operating systems supported : Y

Mac operating systems supported : Y

Manual : Y

Master (outer) case gross weight : 19.3 kg

Master (outer) case height : 135 mm

Master (outer) case length : 833 mm

Master (outer) case net weight : 15.3 kg

Master (outer) case width : 668 mm

Maximum resolution : 1920 x 1200 pixels
Mouse port type : USB, PS/2
Number of computers controlled : 16
Number of users : 512 user(s)
On Screen Display (OSD) : Y
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 50 °C
Package depth : 833 mm
Package height : 135 mm
Package weight : 19.3 kg
Package width : 668 mm
Power consumption (typical) : 26.8 W
Power source : AC
Product colour : Black
Products per master (outer) case : 1 pc(s)
Push button : Y
Rack capacity : 1U
Rack mounting : Y
Scan interval : 1,255 s
Storage temperature (T-T) : -20 - 60 °C
USB connector type : USB Type-A
VGA (D-Sub) ports quantity : 16
Video port type : VGA
Weight : 15.3 kg
Width : 680.4 mm
Windows operating systems supported : Y