

Kvm vga/usb extender kit over CAT5 100M



DESCRIPTION

This extending kit is the ideal tool to use a remote console (VGA monitor/ USB keyboard/ USB mouse) over shielded twisted pair category 5 RJ45 cable, up to 150 meters.

Includes 2 modules, 1 transmitter and 1 receiver, each with its own external power supply.

The transmitter is connected to the PC and can have a local console added.

The receiver allows you to connect a second remote console, VGA monitor, USB keyboard+ mouse

The cat.5 transmitted signal is a user-type signal (not an Ethernet signal) and uses the 4 pairs.

Maximum resolution 1280 x 1024

ASC gain adjustment depending on RJ45 cable length

Automatic and manual switching

1-meter CPU cable included (VGA + USB)

Comes with 2 x 230 V /1.5 A DC external power supplies

All female connectors

Windows and USB supported LINUX compatible

NOT compatible with Macintosh

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : CE700A-AT-G

Caractéristiques :

Type : Transmitter & receiver

AC adapter output voltage : 5.3 V

Cable types supported : Cat5e

Connectivity technology : Wired

Harmonized System (HS) code : 84733080

LED indicators : Link, Power

Manual : Y

Master (outer) case gross weight : 6.86 kg

Master (outer) case height : 194 mm

Master (outer) case length : 336 mm
Master (outer) case net weight : 5.67 kg
Master (outer) case width : 300 mm
Material : Metal
Maximum transfer distance : 150 m
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 50 °C
Package depth : 283 mm
Package height : 173 mm
Package weight : 1.41 kg
Package width : 100 mm
Product colour : Black, Grey
Products per master (outer) case : 5 pc(s)
Quick installation guide : Y
Rack mounting : Y
Receiver depth : 8.14 cm
Receiver height : 2.5 cm
Receiver local keyboard/mouse port type : USB
Receiver local video port type : VGA
Receiver weight : 320 g
Receiver width : 12.7 cm
RJ-45 ports quantity (receiver) : 1
RJ-45 ports quantity (transmitter) : 1
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
Supported resolutions : 1920 x 1200, 1600 x 1200, 1280 x 1024
Transmitter depth : 8.65 cm
Transmitter height : 2.5 cm
Transmitter local keyboard/mouse port type : USB
Transmitter video port type : VGA
Transmitter weight : 330 g
Transmitter width : 12.7 cm
Weight : 1.14 kg