

HANWHA- Anti-ligature corner mount camera 5 Mps TNV-8011C



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : TNV-8011C
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Alarm input/output : Y
Audio input channels : 1
Audio output channels : 1 channels
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Camera shutter speed : 2-1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
Depth : 78.8 mm
Detect distance : 23.6 m
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Fixed focal length : 2.3 mm
Fixed focus : Y
Flash memory : 256 MB

Frame rate : 30 fps
Height : 165 mm
Housing material : Aluminium
Identify distance : 2.4 m
IK code : IK10
Infrared (IR) cut-off filter : Y
Internal memory : 512 MB
International Protection (IP) code : IP66
IP address filtering : Y
Lens viewing angle, diagonal : 174°
Lens viewing angle, horizontal : 131°
Lens viewing angle, vertical : 93.4°
Maximum aperture number : 2.3
Maximum memory card size : 128 GB
Maximum resolution : 2592 x 1944 pixels
Minimum illumination : 0.02 lx
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Noise reduction : Y
Number of cameras : 1
Number of lenses : 1
Number of sensors : 1
Observe distance : 9.4 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Outdoor
Power consumption (Power over Ethernet (PoE)) : 6.49 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : White
Recognize distance : 4.7 m
Security algorithms : EAP-LEAP, EAP-TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, sRTP
Total megapixels : 5 MP
USB port : Y
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711ulaw, G.726
Web-based management : Y
Weight : 830 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Width : 170 mm
Wi-Fi : N