

HANWHA IP camera XNV-8080R



DESCRIPTION

5M Vandal-Resistant Network IR Dome Camera

- Max. 5megapixel (2560 x 1920) resolution
 - 3.9 ~ 9.4mm (2.4x) motorized varifocal lens
 - Max. 30fps@all resolutions (H.265/H.264)
 - H.265 H.264 MJPEG codec supported Multiple streaming
 - Day & Night (ICR) WDR (120dB) Defog
 - Loitering Directional detection Fog detection Audio detection Digital auto tracking Sound classification Tampering
 - Motion detection Handover
 - SD/SDHC/SDXC memory slot (Max. 512GB)
 - Hallway view WiseStream II support
 - IR viewable length 50m IP67/IP66 NEMA 4X IK10
 - LDC support (Lens Distortion Correction)
 - PoE / 24V AC 12V DC Bi-directional audio support
- Features Type Varifocal Internal or External Both Megapixel 5 True Day and Night Yes Image Device 1/1.8 6M CMOS Focal length 3.9 - 9.4 mm Minimum illumination 0.07 lx Weight 1.01 Kg Dimensions W x D x H 160.0 x 118.5 mm

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XNV-8080R

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Vidéo :

Full HD : Y

Détails techniques :

Iris : Y

3D NR (Noise Reduction) : Y

AC input voltage : 24 V

Active tampering alarm : Y

Adjustment shutter speed : Manual
Alarm input/output : Y
Audio detection : Y
Audio system : 2-way
Cabling technology : 10/100Base-T(X)
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y
Diameter : 16 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flip & mirror : Y
Focal length range : 3.9 - 9.4 mm
Focus : Motorized/Manual
Form factor : Dome
Frame rate : 30 fps
Gain control type : Auto/Manual
Height : 118.5 mm
Housing material : Aluminium
IK code : IK10
Image quality adjustment : Contrast
Intelligent Video Surveillance (IVS) system features : Face detection
International Protection (IP) code : IP67
IP address filtering : Y
Languages support : Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
LED type : IR
Mac compatibility : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum aperture number : 1.3
Maximum memory card size : 512 GB
Maximum output level : 1 Vpp
Maximum resolution : 2560 x 1920 pixels
Mounting type : Ceiling
Networking standards : IEEE 802.3af
Night vision : Y
Night vision distance : 50 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 2616 x 1976 pixels
Number of users : 20 user(s)
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 1.8 mm (1 / 1.8»)
Output impedance : 75
Pan range : 0 - 354°
Placement supported : Indoor & outdoor
Power consumption (max) : 14 W
Power consumption (Power over Ethernet (PoE)) : 12.95 W
Power over Ethernet (PoE) : Y

Power source type : PoE
Privacy masking : Y
Product colour : Ivory
Progressive scan : Y
Protection features : Vandal proof
PTZ control : Y
PTZ modes : Digital PTZ
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 2560 x 1440, 2560 x 1920
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Tilt angle range : 0 - 67°
Total megapixels : 5 MP
USB connectivity : Y
USB port : Y
Video compression formats : H.264, H.265, MPEG4
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711, G.711u, G.726
Weight : 1.01 kg
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N
Windows operating systems supported : Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professiona