

HANWHA- Camera QND-6082R1



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QND-6082R1
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Angle of rotation : 355°
Back Light Compensation (BLC) : Y
Built-in HDD : N
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Connectivity technology : Wired
Day/night mode : Y
Diameter : 12 cm
Ethernet LAN : Y
Flash memory : 256 MB
Form factor : Dome
Frame rate : 30 fps
Height : 98.8 mm
Housing material : Plastic
Internal memory : 512 MB
LED type : IR
Maximum aperture number : 2.9
Maximum memory card size : 128 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Mounting type : Ceiling

Night vision : Y
Night vision distance : 20 m
Number of cameras : 1
Number of sensors : 1
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 350°
Power consumption (max) : 6.5 W
Power consumption (Power over Ethernet (PoE)) : 7.7 W
Power consumption (typical) : 6 W
Power source type : DC, PoE
Product colour : White
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 120 dB
Storage temperature (T-T) : -30 - 60 °C
Supported graphics resolutions : 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 800, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP
Tilt angle range : 0 - 67°
Total megapixels : 2 MP
Weight : 320 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N